



COMMERCIAL

Step Up


Carpet Tiles

Technical Specifications

Technische Spezifikationen - Technické specifikace - Specyfikacja techniczna

Construction Structure - Structuur - Konstruktion		5/32" Tip Sheared
Pile fibre composition Composition des fibres - Poolmateriaal - Material der Polnutschicht		100% Duracolor® Premium Nylon (30% recycled content)
Secondary backing Envers - Rug - Beschichtung		EcoFlex™ NXT
Total weight Poids total - Totaal gewicht - Gesamtgewicht		4575 g/m ²
Pile weight Poids du velours - Poolgewicht - Poleinsatzgewicht		1288 g/m ²
Surface pile weight Poids du velours utile - Effectieve poolmassa - Polnutschichtgewicht		754 g/m ²
Total thickness Epaisseur totale - Totale dikte - Gesamtdicke		9 mm
Surface pile thickness Hauteur du velours - Poolhoogte - Poldicke		5,2 mm
Surface pile density Densité du velours - Pooldichtheid - Polrohndichte		0,145 g/cm ³
Number of tufts Nombre de boucles - Aantal noppen - Noppenzahl		93.600/m ²
Wear classification Classement d'usage - Gebruiksklasse - Beanspruchungsklasse	EN 1307	33 / LC3
Castor chair suitability Résistance aux chaises à roulettes - Rolstoelgeschiktheid - Stuhlrolleneignung	EN 985	A: intensive use
Fire classification Comportement au feu - Brandgedrag - Brandklasse	EN 13501-1	Bfl-s1
Dimensional stability Stabilité dimensionnelle - Dimensionele stabiliteit - Dimensionsstabilität	EN 986	≤ 0,2%
Colour fastness to light Solidité des couleurs à la lumière - Lichtbestendigheid van de kleuren - Lichtechtheit	EN ISO 105-B02	≥ 7
Rubbing fastness Solidité au frottement - Wrijftechtheid - Reibechtheit	EN ISO 105-X12	≥ 4
Colour fastness to water Solidité à l'eau - Waterechtheid - Wasserechtheit	EN ISO 105-E01	≥ 4
Thermal resistance Résistance thermique - Warmtedoorlaatweerstand - Wärmedurchlasswiderstand	ISO 8302	0,099 m ² .K/W
Impact sound reduction Réduction phonique aux bruits d'impacts - Reductie contactgeluid - Trittschallverbesserungsmaß	EN ISO 10140-3	ΔLw = 29dB
Permanent antistatic Antistatique permanent - Permanent antistatisch - Permanent antistatisch	ISO 6356	≤ 2 kV
Number of colours Nombre de coloris - Aantal kleuren - Anzahl der Farben		4
Size & Packaging Dimensions & Emballage - Formaat en verpakking - Abmessungen & Verpackung		60,96 cm x 60,96 cm 5,2 m ² /box
GUT-Prodis Number Numéro GUT Prodis - Nummer GUT Prodis - GUT-Prodis Nummer		In progress

We reserve all rights for technical improvements. 12/2020



FLEXLOK